



www.riso.co.za

RETHINK MONOPRINT



RISO SF5350 E

RISO SF5350 E

Master Making/Printing Methods		High-speed digital master-making/Fully automatic printing
Original Type		Book or sheet
Master Making Time*1	Quick Master Making mode	- Approx. 14 seconds (A4, long-edge feed) - Approx. 18 seconds (A4, short-edge feed)
	Normal Master Making mode	- Approx. 16 seconds (A4, long-edge feed) - Approx. 20 seconds (A4, short-edge feed)
Resolution	Scanning	600 dpi × 600 dpi
	Printing	300 dpi × 600 dpi, Quick Master Making mode: 300 dpi × 400 dpi
Maximum Scanning Area		297 mm × 432 mm
Print Paper Weight		46 gsm to 210 gsm
Print Paper Size		100 mm × 148 mm to 310 mm × 432 mm
Maximum Printing Area		291 mm × 413 mm
Paper Feed Tray Stacking Capacity		1000 sheets*2, stacking height of 110 mm or lower
Paper Receiving Tray Stacking Capacity		1000 sheets*2, stacking height of 110 mm or lower
Print Speed		6 levels: 60, 80, 100, 120, 130, and 150 (High Speed *3) ppm
Print Position Adjustment		Horizontal: ±15 mm, Vertical: ±10 mm
Image Processing Mode		Line, Photo, Duo, Pencil
Print Reproduction Ratio		Zoom (50% to 200%), 100% reproduction ratio, 3 levels of enlargement (141%, 122%, 116%), 4 levels of reduction (94%, 87%, 82%, 71%)
User Interface		LCD panel
Functions		Original Scanning Mode, Scanning Level, Enlargement/Reduction, Dot Process, 2-Up, Book, Ink Saving, Quick Master Making, ADF Semi-Auto*4, Speed, Density, Print Position, Program A/B, D-Feed Check, Slip Sheet Sorting, Job Separation*5, Idling, Confidential, Meter Display, Count Report Output, Proof, Direct Printing, USB Flash-via-Printing, Paper Memory Print, Auto Sleep Setting, Auto Power-OFF Setting, ECO Mode, RISO iQuality System
PC Interface		USB2.0, Ethernet:100BASE-TX, 10BASE-T
Ink Supply		Full automatic (1000 ml/cartridge)
Master Supply/Disposal		Full automatic (A3: approx. 220 sheets per roll)/Disposal capacity: approx. 100 sheets
Power Source		AC 100-240 V, 50-60 Hz <3.4-1.6 A>
Power Consumption	Standard	Max.: 300 W, Ready: 20 W or lower, Sleep: 5 W or lower, Power-OFF: 0.5 W or lower
	Optional Accessories Connected*6	Max.: 315 W, Ready: 30 W or lower, Sleep: 10 W or lower, Power-OFF: 0.5 W or lower
Dimensions (W×D×H)	In use	1415 mm × 670 mm*7 × 1065 mm*8
	In storage	780 mm × 670 mm*7 × 1065 mm*8
Required Space (W×D×H)		1415 mm × 1240 mm × 1515 mm*8
Weight		101 kg*9

*1 Measurement value when set to 100% reproduction ratio.

*2 When using the following weight of paper; 64 gsm to 80 gsm

*3 If the temperature of the inside of the print drum (cylinder) is less than 5°C, [High Speed] is not usable.

*4 Usable when the optional auto document feeder is installed.

*5 Usable when the optional Job Separator is installed.

*6 When all the following optional accessories are installed; Auto Document Feeder, Job Separator, IC Card Reader.

*7 The depth does not include the stabilizers for the dedicated stand.

*8 The height includes the dedicated stand.

*9 The weight does not include the ink, master roll, and stand.

Notes: The specifications are subject to change without prior notice.

Optional Accessories



RISO FII Type Drum
Enables color printing.
(Case included)



RISO Auto Document Feeder AF-VII
Scans multiple documents automatically.



RISO Job Separator IV, NIII
Enables easy separation of printed sheets by inserting tape strips.



Card Feed Kit
Compatible with paper weight 100 gsm to 400 gsm.
*Please contact a RISO sales representative for the kinds of paper that may be used.

- IC Card Reader Activation Kit RG
- RISO Network Kit S10

- RISO Printer driver for Macintosh
- Envelope Feed Kit
Compatible with paper weights 50 gsm to 120 gsm.



RISO Power Pedestal
Backup power solution consisting of an inverter and batteries integrated into the machine stand

RISO iQualitySystem™



The RISO i Quality mark indicates a RISO product compatible with the RISO i Quality System.





RISO INK FII Type Color (1000 ml)



RISO MASTER FII Type (A3: 220 sheets)



RISO INK FII Type Black (1000 ml)

 and  RISO, RISO i Quality System and RISO i Quality mark are trademarks or registered trademarks of RISO KAGAKU CORPORATION in the United States and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.
Copyright ©2019 RISO KAGAKU CORPORATION. All rights reserved.



RISO AFRICA (PTY) LTD
<http://www.riso.co.za/>

FOR MORE INFORMATION PLEASE CONTACT



P.O. Box 30300 Lusaka, ZAMBIA
TEL: 00 260 955 801 615
MOB: 00 260 771 282 990 /
00 260 771 282 980