



TRANSFORMING AFRICA'S
PRINT LANDSCAPE SINCE 1994

www.riso.co.za



ENGINE TECHNOLOGY
FORCEJET™

ComColor GL9730



165 ppm

[A4 long-edge feed]



CMYKG
Full color



165
ppm

Print speed
165 ppm



A3

Print size
A3



3 trays



Low energy
consumption



Environmental
certification

Print Type	Line-type inkjet system		
Ink Type	Oil-based pigment ink (Cyan, Magenta, Yellow, Black, Gray)		
Print Resolution	Standard/High Chromogenic	Black: 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray: 300 dpi (main scanning direction) × 300 dpi (sub-scanning direction)	
	Fine	Black: 600 dpi (main scanning direction) × 600 dpi (sub-scanning direction) Cyan, Magenta, Yellow, Gray: 300 dpi (main scanning direction) × 600 dpi (sub-scanning direction)	
Number of Gray Levels	Black: 4 gray levels Cyan, Magenta, Yellow, Gray: 12 gray levels		
Data Processing Resolution	Standard/High Chromogenic	Black: 600 dpi × 600 dpi Cyan, Magenta, Yellow, Gray: 300 dpi × 300 dpi	
	Fine	Black: 600 dpi × 600 dpi Cyan, Magenta, Yellow, Gray: 300 dpi × 600 dpi	
Warm-up Time	2 min. 30 sec. or less (at room temperature of 23°C)		
First Print Time *1	5 sec. or less (A4 Long-edge Feed)		
First Copy Time *1	7 sec. or less (A4 long-edge feed)		
Continuous Print Speed *2*3	A4 Long-edge Feed	Simplex: 165 ppm	Duplex: 82 sheets/minute (164 ppm)
	Letter long-edge feed	Simplex: 160 ppm	Duplex: 80 sheets/minute (160 ppm)
	A4 short-edge feed	Simplex: 120 ppm	Duplex: 60 sheets/minute (120 ppm)
	Letter short-edge feed	Simplex: 120 ppm	Duplex: 60 sheets/minute (120 ppm)
	B4 (JIS) short-edge feed	Simplex: 102 ppm	Duplex: 44 sheets/minute (88 ppm)
	Legal short-edge feed	Simplex: 104 ppm	Duplex: 44 sheets/minute (88 ppm)
	A3 short-edge feed	Simplex: 88 ppm	Duplex: 42 sheets/minute (84 ppm)
	Ledger short-edge feed	Simplex: 86 ppm	Duplex: 42 sheets/minute (84 ppm)
Paper Size	Standard Tray	Maximum: 340 mm × 550 mm	Minimum: 90 mm × 148 mm
	Feed Tray	Maximum: 297 mm × 432 mm	Minimum: 182 mm × 182 mm
Printable Area	314 mm × 548 mm		
Guaranteed Print Area *4	Standard: Margin width of 3 mm		Maximum: Margin width of 1 mm
Paper Weight	Standard Tray	46 gsm to 210 gsm	
	Feed Tray	52 gsm to 104 gsm	
Paper Tray Capacity	Standard Tray	Height up to 110 mm	
	Feed Tray	Height up to 56 mm (x3 trays)	
Output Tray Capacity	Height up to 60 mm		
PDL (Page Description Language)	RISORINC/C IV		
Supported Protocols	TCP/IP, HTTP, HTTPS (TLS), DHCP, ftp, lpr, IPP, SNMP, Port9100 (RAW port), IPv4, IPv6, IPsec		
Network Interface	Ethernet 1000BASE-T, 100BASE-TX, 10BASE-T (2ch)		
Memory Capacity	4 GB		
Hard Disk*8	Capacity	512 GB	
	Available Space	Approx. 370 GB	
Operating System	Linux®		
Power Source	AC 100 V - 240 V, 12.0 A - 6.0 A, 50 Hz - 60 Hz		
Power Consumption	Max. 1,200 W		
	Ready *6: 110 W or less		
	Sleep *7: 2 W or less		
	Stand-by: 0.3 W or less		
	In printing: 490W or less		
Operating Noise	Max. 66 dB (A) A4 long-edge feed (Simplex) at the maximum print speed		
A-weighted Sound Power Level	Max. 79 dB (A) A4 long-edge feed (Simplex) at the maximum print speed		
Operating Environment	Temperature: 15 °C to 30 °C Humidity: 40% to 70% RH (non-condensing)		
Dimensions When Operating (W x D x H)	In use: 1,220 mm × 725 mm × 1,160 mm		
	With cover and tray closed: 1,160 mm × 705 mm × 1,015 mm		
Required Space (W × D × H) *8	1,220 mm × 1,240 mm × 1,160 mm		
Weight	Approx. 177 kg		

*1 Within 10 minutes after the last print job

*2 When using plain paper and recycled paper (85 gsm), and standard density setting.

*3 The continuous print speed varies depending on the type of optional output equipment connected.

*4 The margin when printing envelopes is 10 mm.

*5 The guaranteed area when printing images is the area enclosed within 3 mm of the edges of the paper.

*5 One gigabyte(GB) is calculated as 230 bytes.

*6 Without printing and temperature adjustment operation.

*7 When setting [Power Consumption (In Sleep)] to [Low]

*8 With the front cover open and the operation panel in the upright position

Specifications are subject to change without notice.



ComColor GL Ink Cartridges

Colors: Black, Cyan, Magenta, Yellow, Gray
NET 1,000ml

TRUST THE BRAND YOU KNOW. TRUST RISO.
ALWAYS USE GENUINE CONSUMABLES.

ENVIRONMENTAL
CERTIFICATIONS



FOR MORE DETAILS PLEASE CONTACT

® and RISO. ComColor and FORCEJET are trademarks or registered trademarks of RISO KAGAKU CORPORATION. EFI, Fiery, Fiery Driven and Command WorkStation are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the United States and/or certain other countries. Adobe, Adobe PDF and PostScript are either registered trademarks or trademarks of Adobe in the United States and/or other countries. Microsoft is a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Other corporate names and/or trademarks are either registered trademarks or trademarks of each company, respectively.



RISO AFRICA (PTY) LTD
www.riso.co.za